

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D23-08	7'-8"	22.75	17.27	13.52	10.83	7.33	4	4	0.125
D23-10	9'-8"	18.19	13.69	10.61	8.4	5.53	4	4	0.125
D23-12	11'-8"	14.87	11.06	8.45	6.58	4.14	4	4	0.125
D23-14	13'-8"	12.31	9.00	6.73	5.11	3	4	4	0.125
D23-15	14'-8"	11.23	8.12	5.99	4.47	2.49	4	4	0.125
D24-08	7'-8"	19.29	14.62	11.42	9.14	6.16	4	4	0.125
D24-10	9'-8"	15.35	11.52	8.89	7.01	4.57	4	4	0.125
D24-12	11'-8"	12.47	9.22	6.99	5.40	3.32	4	4	0.125
D24-14	13'-8"	10.22	7.40	5.47	4.09	2.29	4	4	0.125
D24-15	14'-8"	9.27	6.62	4.81	3.51	1.82	4	4	0.125
D25-10	9'-8"	29.3	22.14	17.23	13.72	13.72	5	5	0.155
D25-12	11'-8"	24.16	18.09	13.93	10.95	7.07	5	5	0.155
D25-14	13'-8"	20.23	14.96	11.34	8.76	5.39	5	5	0.155
D25-15	14'-8"	18.57	13.63	10.24	7.81	4.65	5	5	0.155
D25-16	15'-8"	17.08	12.42	9.23	6.94	3.97	5	5	0.155
D30-06	6'-0"	15.25	11.6	9.1	7.31	4.98	3	3	0.125
D30-08	8'-0"	11.7	8.82	6.84	5.43	3.59	3	3	0.125
D30-10	10'-0"	9.27	6.89	5.25	4.09	2.57	3	3	0.125
D30-12	12'-0"	7.45	5.42	4.03	3.04	1.75	3	3	0.125
D31-06	6'-0"	16.36	12.45	9.77	7.85	5.36	3	3	0.125
D31-08	8'-0"	12.58	9.49	7.37	5.86	3.89	3	3	0.125
D31-10	10'-0"	9.99	7.44	5.69	4.44	2.81	3	3	0.125
D31-12	12'-0"	8.07	5.9	4.41	3.34	1.96	3	3	0.125
D32-08	8'-0"	21.92	16.63	13.01	10.42	7.04	4	3	0.125
D32-10	10'-0"	16.03	12.01	9.26	7.29	4.72	4	3	0.125
D32-12	12'-0"	13.27	9.82	7.45	5.76	3.56	4	3	0.125
D32-14	14'-0"	11.15	8.11	6.03	4.55	2.61	4	3	0.125
D33-08	8'-0"	22.34	16.92	13.2	10.54	7.08	4	4	0.125
D33-10	10'-0"	16.11	12.01	9.19	7.18	4.56	4	4	0.125
D33-12	12'-0"	13.28	9.74	7.32	5.58	3.32	4	4	0.125
D33-14	14'-0"	11.03	7.92	5.79	4.26	2.27	4	4	0.125
D34-08	8'-0"	18.43	13.92	10.84	8.63	5.75	4	4	0.125
D34-10	10'-0"	13.15	9.74	7.40	5.73	3.55	4	4	0.125
D34-12	12'-0"	10.73	7.79	5.77	4.33	2.45	4	4	0.125
D34-14	14'-0"	8.78	6.20	4.43	3.16	1.51	4	4	0.125
D37-08	7'-9"	19.90	15.12	11.85	9.51	6.46	4	3	0.125
D37-10	9'-9"	15.90	11.99	9.32	7.40	4.91	4	3	0.125
D37-12	11'-9"	13.02	9.72	7.46	5.84	3.73	4	3	0.125
D37-14	13'-9"	10.83	7.97	6.01	4.60	2.78	4	3	0.125
D37-15	14'-9"	9.90	7.22	5.38	4.07	2.36	4	3	0.125
D38-10	9'-9"	18.69	14.08	10.92	8.65	5.7	4	4	0.125
D38-12	11'-9"	15.3	11.39	8.7	6.79	4.29	4	4	0.125
D38-13	12'-9"	13.92	10.28	7.79	6	3.68	4	4	0.125
D38-14	13'-9"	12.68	9.29	6.96	5.29	3.12	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D38-15	14'-9"	11.58	8.39	6.20	4.64	2.61	4	4	0.125
D39-10	9'-9"	18.2	13.7	10.62	8.41	5.54	4	4	0.125
D39-12	11'-9"	14.88	11.07	8.45	6.58	4.14	4	4	0.125
D39-13	12'-9"	13.53	9.98	7.55	5.81	3.55	4	4	0.125
D39-14	13'-9"	12.32	9.01	6.74	5.11	3	4	4	0.125
D39-15	14'-9"	11.24	8.13	6.00	4.47	2.49	4	4	0.125
D42-08	8'-8"	20.44	15.5	12.11	9.69	6.53	4	3	0.125
D42-10	10'-8"	16.66	12.53	9.7	7.68	5.04	4	3	0.125
D42-12	12'-8"	13.85	10.3	7.87	6.13	3.87	4	3	0.125
D42-14	14'-8"	11.64	8.53	6.4	4.88	2.89	4	3	0.125
D43-08	8'-8"	20.82	15.75	12.28	9.79	6.587	4	4	0.125
D43-10	10'-8"	16.88	12.64	9.74	7.66	4.96	4	4	0.125
D43-12	12'-8"	13.92	10.28	7.79	6.8	3.68	4	4	0.125
D43-14	14'-8"	11.58	8.39	6.2	6	2.61	4	4	0.125
D44-08	8'-8"	20.28	15.34	11.95	9.53	6.37	4	4	0.125
D44-10	10'-8"	16.42	12.3	9.46	7.44	4.8	4	4	0.125
D44-12	12'-8"	13.53	9.98	7.55	5.81	3.55	4	4	0.125
D44-14	14'-8"	11.24	8.13	6	4.47	2.49	4	4	0.125
D48-08	8'-0"	18.97	14.34	11.16	8.90	5.95	4	4	0.125
D48-10	10'-0"	15.13	11.32	8.70	6.83	4.40	4	4	0.125
D48-12	12'-0"	12.31	9.06	6.84	5.24	3.17	4	4	0.125
D48-14	14'-0"	10.10	7.27	5.33	3.95	2.14	4	4	0.125
D49-08	8'-0"	18.47	13.97	10.86	8.66	5.78	4	4	0.125
D49-10	10'-0"	14.72	11.00	8.46	6.63	4.26	4	4	0.125
D49-12	12'-0"	11.96	8.80	6.63	5.07	3.05	4	4	0.125
D49-14	14'-0"	9.80	7.04	5.15	3.80	2.04	4	4	0.125
D50-06	5'-8"	14.62	11.12	8.73	7.01	4.78	3	3	0.125
D50-07	6'-8"	12.75	9.67	7.75	6.03	4.06	3	3	0.125
D50-08	7'-8"	11.28	8.51	6.6	5.24	3.47	3	3	0.125
D50-10	9'-8"	8.99	6.69	5.11	3.97	2.5	3	3	0.125
D50-12	11'-8"	7.27	5.3	3.94	2.97	1.71	3	3	0.125
D51-06	5'-8"	15.13	11.52	9.04	7.27	4.96	3	3	0.125
D51-07	6'-8"	13.21	10.01	7.82	6.26	4.21	3	3	0.125
D51-08	7'-8"	11.69	8.82	6.85	5.44	3.61	3	3	0.125
D51-10	9'-8"	9.33	6.95	5.31	4.14	2.62	3	3	0.125
D51-12	11'-8"	7.56	5.52	4.12	3.12	1.81	3	3	0.125
D52-06	5'-8"	15.23	11.62	9.14	7.37	5.06	4	3	0.125
D52-07	6'-8"	13.35	10.16	7.97	6.40	4.36	4	3	0.125
D52-08	7'-8"	11.88	9.01	7.04	5.63	3.80	4	3	0.125
D52-10	9'-8"	9.62	7.24	5.60	4.43	2.90	4	3	0.125
D52-12	11'-8"	7.95	5.91	4.51	3.51	2.20	4	3	0.125
D53-06	5'-8"	23.52	17.92	14.08	11.33	7.75	4	4	0.125
D53-07	6'-8"	20.57	15.61	12.22	9.79	6.63	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D53-08	7'-8"	18.24	13.79	10.74	8.56	5.71	4	4	0.125
D53-10	9'-8"	14.65	10.95	8.42	6.60	4.24	4	4	0.125
D53-12	11'-8"	11.97	8.80	6.63	5.08	3.06	4	4	0.125
D54-06	5'-8"	22.92	17.46	13.71	11.03	7.54	4	4	0.125
D54-07	6'-8"	20.04	15.21	11.90	9.53	6.45	4	4	0.125
D54-08	7'-8"	17.77	13.43	10.45	8.32	5.55	4	4	0.125
D54-10	9'-8"	14.26	10.65	9.79	6.41	4.10	4	4	0.125
D54-12	11'-8"	11.63	8.54	7.81	4.91	2.94	4	4	0.125
D55-08	8'-3"	26.04	19.83	15.57	12.53	8.56	3.5	3.5	0.125
D55-09	9'-3"	23.43	17.79	13.93	11.17	7.57	3.5	3.5	0.125
D55-10	10'-3"	21.22	16.07	12.53	10.01	6.71	3.5	3.5	0.125
D55-12	12'-3"	17.69	13.28	10.26	8.1	5.29	3.5	3.5	0.125
D55N-08	8'-3"	21.49	16.28	12.73	10.19	6.88	4	4	0.125
D55N-09	9'-3"	19.21	14.52	11.3	9	6	4	4	0.125
D55N-10	10'-3"	17.31	13.01	10.07	7.97	5.23	4	4	0.125
D55N-12	12'-3"	14.24	10.57	8.06	6.26	3.92	4	4	0.125
D58-08	8'-3"	18.21	13.78	10.75	8.59	5.77	4	4	0.125
D58-09	9'-3"	16.25	12.25	9.51	7.54	4.99	4	4	0.125
D58-10	10'-3"	14.60	10.94	8.43	6.64	4.30	4	4	0.125
D58-12	12'-3"	11.92	8.80	6.66	5.13	3.13	4	4	0.125
D67-08	8'-0"	21.75	16.46	12.48	10.24	6.87	4	3	0.125
D67-10	10'-0"	17.49	13.12	10.13	7.99	5.2	4	3	0.125
D67-12	12'-0"	14.39	10.67	8.12	6.29	3.42	4	3	0.125
D67-14	14'-0"	11.99	8.75	6.53	4.94	2.87	4	3	0.125
D69-08	8'-0"	21.54	16.26	12.63	10.04	6.67	4	4	0.125
D69-10	10'-0"	19.19	14.41	11.13	8.78	5.73	4	4	0.125
D69-12	12'-0"	17.20	12.84	9.84	7.70	4.91	4	4	0.125
D69-14	14'-0"	14.02	10.30	7.75	5.92	3.55	4	4	0.125
D70-05	5'-6"	16.29	12.38	9.7	7.78	5.29	3	3	0.125
D70-06	6'-6"	14.06	10.64	8.3	6.62	4.43	3	3	0.125
D70-07	7'-6"	12.29	9.25	7.17	5.68	3.73	3	3	0.125
D70-08	8'-6"	10.84	8.11	6.23	4.89	3.14	3	3	0.125
D71-05	5'-6"	16.87	12.82	10.05	8.07	5.48	3	3	0.125
D71-06	6'-6"	14.57	11.03	8.6	6.87	4.61	3	3	0.125
D71-07	7'-6"	12.74	9.6	7.44	5.9	3.89	3	3	0.125
D71-08	8'-6"	11.25	8.41	6.47	5.09	3.28	3	3	0.125
D77-08	8'-4"	21.77	16.56	13.00	10.45	7.12	4	3	0.125
D77-10	10'-4"	17.76	13.44	10.47	8.35	5.58	4	3	0.125
D77-12	12'-4"	14.82	11.11	8.57	6.75	4.39	4	3	0.125
D77-13	13'-4"	13.61	10.15	7.78	6.08	3.88	4	3	0.125
D77-14	14'-4"	12.53	9.29	7.07	5.48	3.41	4	3	0.125
D77-15	15'-4"	11.55	8.51	6.42	4.92	2.97	4	3	0.125
D78-08	8'-4"	21.62	16.42	12.85	10.3	6.98	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D78-10	10'-4"	17.53	13.2	10.24	8.11	5.35	4	4	0.125
D78-12	12'-4"	14.49	10.28	8.24	6.42	4.06	4	4	0.125
D78-13	13'-4"	13.23	9.77	7.4	5.7	3.5	4	4	0.125
D78-14	14'-4"	12.09	8.85	6.63	5.05	2.98	4	4	0.125
D78-15	15'-4"	11.07	8.02	5.93	4.44	2.49	4	4	0.125
D79-08	8'-4"	21.07	16	12.52	10.03	6.79	4	4	0.125
D79-10	10'-4"	17.07	12.85	9.96	7.89	5.19	4	4	0.125
D79-12	12'-4"	14.09	10.48	8	6.23	3.92	4	4	0.125
D79-13	13'-4"	12.86	9.49	7.18	5.52	3.37	4	4	0.125
D79-14	14'-4"	11.75	8.59	6.42	4.88	2.86	4	4	0.125
D79-15	15'-4"	10.74	7.77	5.74	4.28	2.38	4	4	0.125
D87-08	7'-7"	22.98	17.46	13.68	10.97	7.45	4	3	0.125
D87-10	9'-7"	18.44	13.92	10.81	8.60	5.71	4	3	0.125
D87-12	11'-7"	15.18	11.35	8.72	6.84	4.39	4	3	0.125
D87-14	13'-7"	12.70	9.37	7.09	5.46	3.34	4	3	0.125
D88-08	7'-7"	23.39	17.73	13.85	11.08	7.46	4	4	0.125
D88-10	9'-7"	18.65	14.01	10.83	8.55	5.59	4	4	0.125
D88-12	11'-7"	15.21	11.28	8.58	6.66	4.14	4	4	0.125
D88-14	13'-7"	12.57	9.15	6.82	5.14	2.96	4	4	0.125
D89-08	7'-7"	22.79	17.27	13.49	10.78	7.26	4	4	0.125
D89-10	9'-7"	18.15	13.63	10.53	8.31	5.42	4	4	0.125
D89-12	11'-7"	14.79	10.96	8.33	6.45	4	4	4	0.125
D89-14	13'-7"	12.2	8.88	6.6	4.97	2.84	4	4	0.125
D92-08	7'-9"	22.72	17.29	13.57	10.91	7.44	4	3	0.125
D92-10	9'-9"	18.22	13.77	10.73	8.55	5.71	4	3	0.125
D92-12	11'-9"	15.05	11.28	8.69	6.84	4.42	4	3	0.125
D92-13	12'-9"	13.76	10.25	7.84	6.12	3.88	4	3	0.125
D92-14	13'-9"	12.62	9.34	7.09	5.48	3.38	4	3	0.125
D93-08	7'-9"	23.2	17.63	13.82	11.09	7.53	4	4	0.125
D93-10	9'-9"	18.52	13.96	10.84	8.6	5.69	4	4	0.125
D93-12	11'-9"	15.2	11.33	8.67	6.77	4.3	4	4	0.125
D93-13	12'-9"	13.84	10.24	7.77	6.01	3.71	4	4	0.125
D93-14	13'-9"	12.63	9.27	6.96	5.31	3.16	4	4	0.125
D94-08	7'-9"	22.61	17.18	13.46	10.8	7.33	4	4	0.125
D94-10	9'-9"	18.03	13.59	10.54	8.36	5.52	4	4	0.125
D94-12	11'-9"	14.79	11.01	8.42	6.57	4.16	4	4	0.125
D94-13	12'-9"	13.46	9.95	7.54	5.82	3.57	4	4	0.125
D94-14	13'-9"	12.27	8.99	6.74	5.13	3.04	4	4	0.125
D95-10	10'-1"	35.31	26.75	20.87	16.67	11.2	5	5	0.155
D95-12	12'-1"	29.44	22.14	17.13	13.55	8.88	5	5	0.155
D95-13	13'-1"	27.05	20.25	15.58	12.25	7.9	5	5	0.155
D95-14	14'-1"	24.93	18.56	14.2	11.08	7.01	5	5	0.155
D95-15	15'-1"	23.03	17.05	12.95	10.01	6.19	5	5	0.155
D1003S14-08	8'-0"	19.18	14.50	11.28	8.98	5.99	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D1003S14-10	10'-0'	15.33	11.46	8.82	6.92	4.45	4	4	0.125
D1003S14-12	12'-0'	12.52	9.23	6.98	5.37	3.27	4	4	0.125
D1004S14-08	8'-0"	18.68	14.11	10.98	8.74	5.82	4	4	0.125
D1004S14-10	10'-0'	14.92	11.15	8.57	6.72	4.31	4	4	0.125
D1004S14-12	12'-0'	12.17	8.96	6.77	5.20	3.15	4	4	0.125
D1005S14-08	8'-0"	30.03	22.75	17.76	14.19	9.54	4	4	0.125
D1005S14-10	10'-0'	24.15	18.15	14.04	11.10	7.26	4	4	0.125
D1005S14-12	12'-0'	19.89	14.79	11.29	8.79	5.53	4	4	0.125
D1005S14-14	14'-0'	16.62	12.18	9.14	6.97	4.13	4	4	0.125
D1103-06	5'-7"	28.04	21.3	16.67	13.37	9.06	4	4	0.125
D1103-08	7'-7"	21.76	16.4	12.72	10.09	6.66	4	4	0.125
D1103-10	9'-7"	17.32	12.9	9.86	7.69	4.87	4	4	0.125
D1103-12	11'-7"	14.12	10.34	7.76	5.90	3.49	4	4	0.125
D1104-06	5'-7"	27.32	20.75	16.24	13.02	8.82	4	4	0.125
D1104-08	7'-7"	21.19	15.96	12.38	9.81	6.47	4	4	0.125
D1104-10	9'-7"	16.85	12.53	9.58	7.46	4.71	4	4	0.125
D1104-12	11'-7"	13.72	10.04	7.51	5.71	3.35	4	4	0.125
D1303-08	7'-7"	23.51	17.79	13.86	11.06	7.4	4	4	0.125
D1303-10	9'-7"	18.66	13.97	10.76	8.47	5.48	4	4	0.125
D1303-12	11'-7"	15.16	11.2	8.48	6.54	4.01	4	4	0.125
D1303-14	13'-7"	12.47	9.04	6.68	5.00	2.81	4	4	0.125
D1304-08	7'-7"	22.90	17.32	13.49	10.76	7.19	4	4	0.125
D1304-10	9'-7"	18.16	13.59	10.46	8.22	5.31	4	4	0.125
D1304-12	11'-7"	14.74	10.87	8.22	6.33	3.86	4	4	0.125
D1304-14	13'-7"	12.11	8.76	6.46	4.82	2.68	4	4	0.125
D1305-08	7'-7"	45.97	34.93	27.36	21.94	14.89	5	5	0.155
D1305-10	9'-7"	36.89	27.85	21.66	17.23	11.46	5	5	0.155
D1305-12	11'-7"	30.43	22.78	17.54	13.8	8.91	5	5	0.155
D1305-14	13'-7"	25.54	18.91	14.37	11.12	6.89	5	5	0.155
D1305-15	14'-7"	23.5	17.29	13.03	9.99	6.02	5	5	0.155
D1405-10	10'-0"	29.83	22.47	17.42	13.81	9.11	5	5	0.155
D1405-12	12'-0"	24.65	18.38	14.08	11.01	7.00	5	5	0.155
D1405-14	14'-0"	20.67	15.21	11.46	8.78	5.29	5	5	0.155
D1405-16	16'-0"	17.46	12.63	9.31	6.94	3.85	5	5	0.155
D1903-08	8'-5"	19.99	15.09	11.73	9.33	6.20	4	4	0.125
D1903-10	10'-5"	15.76	11.75	9.01	7.05	4.47	4	4	0.125
D1903-12	12'-5"	12.70	9.31	6.99	5.33	3.17	4	4	0.125
D1903-14	14'-5"	10.33	7.40	5.39	3.95	2.08	4	4	0.125
D1903-15	15'-5"	8.14	5.62	3.89	2.65	1.04	4	4	0.125
D1904-08	8'-5"	19.47	14.69	11.41	9.07	6.02	4	4	0.125
D1904-10	10'-5"	15.33	11.43	8.75	6.84	4.33	4	4	0.125
D1904-12	12'-5"	12.34	9.03	6.77	5.15	3.04	4	4	0.125
D1904-14	14'-5"	10.02	7.16	5.20	3.80	1.97	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D1904-15	15'-5"	8.42	5.83	4.06	2.79	1.13	4	4	0.125
D1905-08	8'-5"	27.92	20.95	16.26	12.91	8.54	5	5	0.155
D1905-10	10'-5"	22.38	16.69	12.78	9.99	6.35	5	5	0.155
D1905-12	12'-5"	18.36	13.48	10.14	7.75	4.63	5	5	0.155
D1905-14	14'-5"	15.21	10.94	8.02	5.92	3.19	5	5	0.155
D1905-16	16'-5"	12.63	8.84	6.24	4.38	1.95	5	5	0.155
D1910	10'-1"	34.17	25.52	19.80	15.70	10.37	6	4	0.25
D1912	12'-0"	28.81	21.18	16.27	12.75	8.18	6	4	0.25
D1914	13'-8"	25.12	18.11	13.75	10.63	6.57	6	4	0.25
D2122-08	8'-2"	18.38	13.94	10.90	8.73	5.90	4	3	0.125
D2122-10	10'-2"	14.87	11.20	8.68	6.88	4.53	4	3	0.125
D2122-12	12'-2"	12.30	9.16	7.02	5.48	3.48	4	3	0.125
D2122-13	13'-2"	11.25	8.33	6.27	4.89	3.03	4	3	0.125
D2122-14	14'-2"	10.31	7.58	5.70	4.36	2.61	4	3	0.125
D2123-08	8'-2"	18.58	14.04	10.92	8.69	5.78	4	4	0.125
D2123-10	10'-2"	14.86	11.09	8.51	6.66	4.25	4	4	0.125
D2123-12	12'-2"	12.09	8.87	6.67	5.09	3.04	4	4	0.125
D2123-13	13'-2"	10.94	7.95	5.83	4.42	2.40	4	4	0.125
D2123-14	14'-2"	9.91	7.11	5.18	3.81	2.02	4	4	0.125
D2124-08	8'-2"	18.10	13.67	10.63	8.45	5.62	4	4	0.125
D2124-10	10'-2"	14.45	10.78	8.26	6.46	4.12	4	4	0.125
D2124-12	12'-2"	11.74	8.61	6.46	4.92	2.92	4	4	0.125
D2124-13	13'-2"	10.62	7.70	5.63	4.27	2.40	4	4	0.125
D2124-14	14'-2"	9.61	6.88	5.00	3.66	1.92	4	4	0.125
D2125-10	10'-2"	28.86	21.74	16.86	13.37	8.82	5	5	0.155
D2125-12	12'-2"	23.90	17.82	13.65	10.67	6.79	5	5	0.155
D2125-13	13'-2"	21.86	16.20	12.20	9.54	5.92	5	5	0.155
D2125-14	14'-2"	20.05	14.75	11.12	8.52	5.13	5	5	0.155
D2125-16	16'-2"	16.95	12.25	9.03	6.72	3.72	5	5	0.155
D2600-08	8'-0"	10.46	7.86	6.08	4.81	3.15	3	3	0.125
D2600-10	10'-0"	8.28	6.12	4.65	3.59	2.21	3	3	0.125
D2600-12	12'-0"	6.64	4.79	3.53	2.62	1.44	3	3	0.125
D2600-14	14'-0"	5.32	3.71	2.61	3.66	0.79	3	3	0.125
D2601-08	8'-0"	9.54	7.16	5.52	4.35	2.83	3	3	0.125
D2601-10	10'-0"	7.52	5.54	4.18	3.21	1.95	3	3	0.125
D2601-12	12'-0"	5.98	4.29	3.13	2.30	1.22	3	3	0.125
D2601-14	14'-0"	4.75	3.27	2.26	1.54	0.59	3	3	0.125
D2602-08	8'-0"	18.09	13.73	10.73	8.59	5.79	4	3	0.125
D2602-10	10'-0"	14.67	11.04	8.55	6.77	4.46	4	3	0.125
D2602-12	12'-0"	12.15	9.05	6.92	5.40	3.42	4	3	0.125
D2602-14	14'-0"	10.20	7.49	5.63	4.30	2.57	4	3	0.125
D2602-16	16'-0"	8.61	6.21	4.56	3.38	1.84	4	3	0.125
D2603-08	8'-0"	18.29	13.81	10.74	8.54	5.67	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D2603-10	10'-0"	14.65	10.93	8.38	6.55	4.17	4	4	0.125
D2603-12	12'-0"	11.93	8.75	6.57	5.01	2.98	4	4	0.125
D2603-14	14'-0"	9.79	7.01	5.10	3.74	2.57	4	4	0.125
D2603-16	16'-0"	8.03	5.56	3.87	2.66	0.99	4	4	0.125
D2604-08	8'-0"	17.81	13.44	10.45	8.30	5.51	4	4	0.125
D2604-10	10'-0"	14.25	10.62	8.14	6.36	4.04	4	4	0.125
D2604-12	12'-0"	11.59	8.49	6.36	4.84	2.86	4	4	0.125
D2604-14	14'-0"	9.49	6.78	4.93	3.60	2.57	4	4	0.125
D2604-16	16'-0"	7.76	5.36	3.71	2.53	0.89	4	4	0.125
D4030-08	8'-4"	11.64	8.84	6.93	5.56	3.78	3	3	0.125
D4030-10	10'-4"	9.38	7.06	5.47	4.33	2.85	3	3	0.125
D4030-12	12'-4"	7.67	5.69	4.33	3.36	2.09	3	3	0.125
D4030-14	14'-4"	6.31	4.58	3.39	2.54	1.44	3	3	0.125
D4031-08	8'-4"	12.05	9.16	7.18	5.76	3.92	3	3	0.125
D4031-10	10'-4"	9.72	7.32	5.67	4.5	2.96	3	3	0.125
D4031-12	12'-4"	7.96	5.91	4.51	3.5	2.19	3	3	0.125
D4031-14	14'-4"	6.57	4.78	3.55	2.67	1.52	3	3	0.125
D4032-08	8'-4"	21.57	16.44	12.93	10.42	7.14	4	3	0.125
D4032-10	10'-4"	17.6	13.35	10.43	8.34	5.62	4	3	0.125
D4032-12	12'-4"	14.68	11.04	8.55	6.77	4.44	4	3	0.125
D4032-14	14'-4"	12.41	9.23	7.05	5.5	3.47	4	3	0.125
D4032-16	16'-4"	10.57	7.75	5.81	4.43	2.63	4	3	0.125
D4033-08	8'-4"	22.05	16.8	13.19	10.62	7.26	4	4	0.125
D4033-10	10'-4"	17.93	13.57	10.57	8.43	5.64	4	4	0.125
D4033-12	12'-4"	14.87	11.14	8.58	6.75	4.37	4	4	0.125
D4033-14	14'-4"	12.47	9.21	6.98	5.38	3.3	4	4	0.125
D4033-16	16'-4"	10.51	7.62	5.63	4.21	2.37	4	4	0.125
D4034-08	8'-4"	21.49	16.37	12.85	10.34	7.07	4	4	0.125
D4034-10	10'-4"	17.46	13.21	10.29	8.20	5.49	4	4	0.125
D4034-12	12'-4"	14.47	10.83	8.34	6.56	4.23	4	4	0.125
D4034-14	14'-4"	12.12	8.95	6.77	5.21	3.18	4	4	0.125
D4034-16	16'-4"	10.20	7.38	5.45	4.06	2.26	4	4	0.125
D4070-08	7'-10"	12.25	9.31	7.29	5.85	3.98	3	3	0.125
D4070-10	9'-10"	9.78	7.36	5.7	4.52	2.97	3	3	0.125
D4070-12	11'-10"	7.95	5.9	4.49	3.48	2.17	3	3	0.125
D4071-08	7'-10"	12.68	9.64	7.56	6.07	4.12	3	3	0.125
D4071-10	9'-10"	10.14	7.64	5.92	4.69	3.09	3	3	0.125
D4071-12	11'-10"	8.26	6.13	4.67	3.63	2.27	3	3	0.125
D4072-08	7'-10"	12.31	9.37	7.35	5.91	4.03	4	3	0.125
D4072-10	9'-10"	9.89	7.47	5.81	4.63	3.08	4	3	0.125
D4072-12	11'-10"	8.12	6.06	4.65	3.64	2.33	4	3	0.125
D4072-14	13'-10"	6.74	4.95	3.72	2.85	1.71	4	3	0.125
D4073-08	7'-10"	23.21	17.68	13.89	11.18	7.64	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D4073-10	9'-10"	18.71	14.15	11.03	8.80	5.89	4	4	0.125
D4073-12	11'-10"	15.42	11.55	8.90	7.00	4.53	4	4	0.125
D4073-14	13'-10"	12.87	9.51	7.20	5.55	3.40	4	4	0.125
D4074-08	7'-10"	22.62	17.23	13.53	10.89	7.44	4	4	0.125
D4074-10	9'-10"	18.22	13.78	10.74	8.56	5.72	4	4	0.125
D4074-12	11'-10"	15.01	11.23	8.65	6.80	4.39	4	4	0.125
D4074-14	13'-10"	12.51	9.23	6.98	5.38	3.28	4	4	0.125
D7502-08	8'-5"	21.60	16.45	12.92	10.39	7.10	4	3	0.125
D7502-10	10'-5"	17.68	13.38	10.44	8.34	5.59	4	3	0.125
D7502-12	12'-5"	14.78	11.11	8.57	6.75	4.39	4	3	0.125
D7502-13	13'-5"	13.58	10.15	7.79	6.11	3.92	4	3	0.125
D7502-14	14'-5"	12.52	9.30	7.09	5.51	3.46	4	3	0.125
D7503-08	8'-5"	21.39	13.83	10.83	10.27	5.87	4	4	0.125
D7503-10	10'-5"	14.75	11.10	8.59	6.80	4.46	4	4	0.125
D7503-12	12'-5"	12.15	8.99	6.83	5.28	3.26	4	4	0.125
D7503-13	13'-5"	11.06	8.13	6.13	4.69	2.82	4	4	0.125
D7503-14	14'-5"	10.08	7.34	5.46	4.11	2.36	4	4	0.125
D7504-08	8'-5"	20.84	13.48	10.54	10.00	5.71	4	4	0.125
D7504-10	10'-5"	14.36	10.80	8.35	6.61	4.33	4	4	0.125
D7504-12	12'-5"	11.81	8.73	6.62	5.11	3.15	4	4	0.125
D7504-13	13'-5"	10.75	7.89	5.94	4.54	2.72	4	4	0.125
D7504-14	14'-5"	9.79	7.11	5.28	3.97	2.26	4	4	0.125
D7505-10	10'-5"	31.71	24.03	16.78	15.00	10.09	5	5	0.155
D7505-12	12'-5"	21.54	20.01	15.46	12.21	7.98	5	5	0.155
D7505-14	14'-5"	22.55	16.79	12.84	10.02	6.34	5	5	0.155
D7505-15	15'-5"	20.85	15.43	11.71	9.05	5.59	5	5	0.155
D7505-16	16'-5"	19.31	14.19	10.68	8.17	4.89	5	5	0.155
D7506-10	10'-5"	28.44	21.52	16.78	13.39	8.98	5	5	0.155
D7506-12	12'-5"	19.23	17.84	13.75	10.83	7.01	5	5	0.155
D7506-14	14'-5"	20.09	14.91	11.35	8.81	5.50	5	5	0.155
D7506-15	15'-5"	18.54	13.66	10.31	7.92	4.80	5	5	0.155
D7506-16	16'-5"	17.12	12.51	9.36	7.09	4.15	5	5	0.155
D8502-08	7'-8"	23.58	18.05	14.18	11.42	7.81	4	3	0.125
D8502-10	9'-8"	19.10	14.47	11.30	9.03	6.07	4	3	0.125
D8502-12	11'-8"	15.80	11.88	9.19	7.26	4.76	4	3	0.125
D8502-14	13'-8"	13.28	9.88	7.55	5.88	3.70	4	3	0.125
D8502-16	15'-8"	11.28	8.27	6.21	4.73	2.81	4	3	0.125
D8503-08	7'-8"	23.36	15.20	11.90	11.29	6.48	4	4	0.125
D8503-10	9'-8"	15.96	12.02	9.32	7.38	4.86	4	4	0.125
D8503-12	11'-8"	13.01	9.67	7.38	5.74	3.60	4	4	0.125
D8503-14	13'-8"	10.72	7.82	5.83	4.41	2.56	4	4	0.125
D8503-16	15'-8"	8.86	6.30	4.54	3.29	1.65	4	4	0.125
D8504-08	7'-8"	22.77	14.81	11.59	11.00	6.30	4	4	0.125
D8504-10	9'-8"	15.54	11.70	9.06	7.18	4.72	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D8504-12	11'-8"	12.66	9.40	7.16	5.56	3.48	4	4	0.125
D8504-14	13'-8"	10.41	7.58	5.65	4.26	2.45	4	4	0.125
D8504-16	15'-8"	8.59	6.09	4.38	3.15	1.56	4	4	0.125
D8505-08	7'-8"	39.57	30.29	23.80	19.16	13.11	5	5	0.155
D8505-10	9'-8"	32.05	24.29	18.96	15.16	10.20	5	5	0.155
D8505-12	11'-8"	26.52	19.94	15.43	12.20	8.00	5	5	0.155
D8505-14	13'-8"	22.30	16.59	12.68	9.87	6.23	5	5	0.155
D8505-16	15'-8"	18.94	13.89	10.43	7.96	4.74	5	5	0.155
D8506-08	7'-8"	37.96	29.05	22.82	18.37	12.56	5	5	0.155
D8506-10	9'-8"	30.73	23.27	18.16	14.51	9.75	5	5	0.155
D8506-12	11'-8"	25.40	19.08	14.75	11.65	7.61	5	5	0.155
D8506-14	13'-8"	21.33	15.85	12.09	9.40	5.89	5	5	0.155
D8506-16	15'-8"	18.08	13.23	9.91	7.54	4.44	5	5	0.155
D9003-08	7'-7"	19.26	14.64	11.47	9.21	6.26	4	4	0.125
D9003-10	9'-7"	15.49	11.67	9.06	7.19	4.75	4	4	0.125
D9003-12	11'-7"	12.70	9.45	7.22	5.63	3.55	4	4	0.125
D9003-14	13'-7"	10.52	7.69	5.74	4.36	2.55	4	4	0.125
D9003-15	14'-7"	9.58	6.92	5.10	3.79	2.10	4	4	0.125
D9004-08	7'-7"	18.77	14.26	11.18	8.97	6.09	4	4	0.125
D9004-10	9'-7"	15.08	11.36	8.81	6.99	4.61	4	4	0.125
D9004-12	11'-7"	12.36	9.19	7.01	5.46	3.43	4	4	0.125
D9004-14	13'-7"	10.21	7.45	5.56	4.21	2.44	4	4	0.125
D9004-15	14'-7"	9.30	6.70	4.93	3.66	2.00	4	4	0.125
D9005-10	9'-7"	29.79	22.58	17.63	17.86	9.48	5	5	0.155
D9005-12	11'-7"	24.76	18.62	14.40	11.39	7.46	5	5	0.155
D9005-14	13'-7"	20.88	15.19	11.86	9.24	5.82	5	5	0.155
D9005-15	14'-7"	19.24	14.22	10.77	8.30	5.09	5	5	0.155
D9005-16	15'-7"	17.76	13.02	9.77	7.45	4.42	5	5	0.155
DFS9103-08	8'-0"	19.33	14.71	11.54	9.28	6.32	4	4	0.125
DFS9103-10	10'-0"	15.57	11.76	9.14	7.27	4.83	4	4	0.125
DFS9103-12	12'-0"	12.79	9.54	7.31	5.72	3.64	4	4	0.125
DFS9103-14	14'-0"	10.62	7.78	5.84	4.46	2.65	4	4	0.125
DFS9103-15	15'-0"	9.68	7.02	5.20	3.90	2.20	4	4	0.125
DFS9104-08	8'-0"	18.83	14.33	11.24	9.03	6.16	4	4	0.125
DFS9104-10	10'-0"	15.16	11.44	8.89	7.07	4.69	4	4	0.125
DFS9104-12	12'-0"	12.45	9.28	7.10	5.55	3.53	4	4	0.125
DFS9104-14	14'-0"	10.31	7.55	5.66	4.31	2.54	4	4	0.125
DFS9104-15	15'-0"	9.40	6.81	5.03	3.76	2.10	4	4	0.125
DFS9105-10	10'-0"	29.89	22.68	17.73	14.19	9.59	5	5	0.155
DFS9105-12	12'-0"	24.88	18.73	14.52	11.50	7.58	5	5	0.155
DFS9105-14	14'-0"	21.01	15.65	11.99	9.36	5.94	5	5	0.155
DFS9105-15	15'-0"	19.37	14.34	10.90	8.43	5.22	5	5	0.155
DFS9105-16	16'-0"	17.89	13.15	9.90	7.58	4.55	5	5	0.155
DSD1703-08	7'-8"	18.83	14.21	11.04	8.77	5.82	4	4	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
DSD1703-10	9'-8"	14.99	11.18	8.56	6.69	4.25	4	4	0.125
DSD1703-12	11'-8"	12.16	8.91	6.68	5.09	3.01	4	4	0.125
DSD1703-14	13'-8"	9.94	7.11	5.17	3.78	1.97	4	4	0.125
DSD1704-08	7'-8"	18.33	13.83	10.74	8.53	5.66	4	4	0.125
DSD1704-10	9'-8"	14.59	10.86	8.31	6.49	4.11	4	4	0.125
DSD1704-12	11'-8"	11.81	8.64	6.47	4.92	2.89	4	4	0.125
DSD1704-14	13'-8"	9.64	6.88	4.99	3.63	1.87	4	4	0.125
DSD1705-08	7'-8"	36.15	27.42	21.44	17.15	11.57	4	4	0.125
DSD1705-10	9'-8"	29.17	21.95	17.01	13.47	8.86	4	4	0.125
DSD1705-12	11'-8"	24.08	17.94	13.73	10.71	6.79	4	4	0.125
DSD1705-14	13'-8"	20.17	14.81	11.14	8.52	5.10	4	4	0.125
DSD1705-15	14'-8"	18.51	13.48	10.04	7.57	4.36	4	4	0.125
DSD2005-10	9'-8"	29.51	22.30	17.35	13.82	9.21	5	5	0.155
DSD2005-12	11'-8"	24.45	18.31	14.10	11.08	7.16	5	5	0.155
DSD2005-14	13'-8"	20.56	15.20	11.53	8.91	5.49	5	5	0.155
DSD2005-15	14'-8"	18.91	13.88	10.43	7.97	4.76	5	5	0.155
DSD2005-16	15'-8"	17.42	12.68	9.43	7.10	4.07	5	5	0.155
DU4103-08	7'-8"	19.42	14.80	11.63	9.36	6.41	4	4	0.125
DU4103-10	9'-8"	15.68	11.87	9.25	7.38	4.94	4	4	0.125
DU4103-12	11'-8"	12.92	9.67	7.44	5.85	3.77	4	4	0.125
DU4103-14	13'-8"	10.76	7.93	5.99	4.60	2.79	4	4	0.125
DU4103-16	15'-8"	8.98	6.48	4.76	3.53	1.93	4	4	0.125
DU4104-08	7'-8"	18.92	14.42	11.33	9.12	6.25	4	4	0.125
DU4104-10	9'-8"	15.28	11.56	9.01	7.18	4.80	4	4	0.125
DU4104-12	11'-8"	12.58	9.41	7.24	5.68	3.66	4	4	0.125
DU4104-14	13'-8"	10.46	7.70	5.80	4.45	2.69	4	4	0.125
DU4104-16	15'-8"	8.72	6.27	4.60	3.40	1.84	4	4	0.125
EA6-08	08'-0"	21.96	16.67	13.05	10.45	7.08	4	4	0.125
EA6-10	10'-0"	17.66	13.3	10.3	8.16	5.37	4	4	0.125
EA6-12	12'-0"	14.51	10.79	8.24	6.42	4.04	4	4	0.125
EA6-14	14'-0"	12.05	8.81	6.59	5	2.93	4	4	0.125
EA6-15	15'-0"	11	7.96	5.88	4.38	2.44	4	4	0.125
EA6-16	16'-0"	10.05	7.18	5.22	3.81	1.98	4	4	0.125
EA6F-08	8'-0"	22.53	17.11	13.40	10.74	7.27	4	4	0.125
EA6F-10	10'-0"	18.14	13.66	10.59	8.4	5.54	4	4	0.125
EA6F-12	12'-0"	14.92	11.1	8.49	6.61	4.18	4	4	0.125
EA6F-14	14'-0"	12.41	9.08	6.81	5.18	3.05	4	4	0.125
EA6F-15	15'-0"	11.34	8.22	6.08	4.55	2.55	4	4	0.125
DPO/PLT-06	6'-0"	14.75	11.10	8.60	6.81	4.48	3	3	0.125
DPO/PLT-08	8'-0"	11.15	8.26	6.29	4.88	3.04	3	3	0.125
DPO/PLT-10	10'-0"	8.67	6.29	4.66	3.50	1.98	3	3	0.125
FPO3/PLT-06	6'-0"	12.91	9.69	7.26	5.95	3.85	3	3	0.125
FPO3/PLT-08	8'-0"	9.69	7.15	5.44	4.18	2.54	3	3	0.125
FPO3/PLT-10	10'-0"	9.02	6.56	4.90	3.68	2.09	3	3	0.125

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
DPO65-10	10'-0"	10.45	7.71	5.83	4.49	2.74	3	3	0.065
DPO-12	12'-0"	8.17	5.89	4.32	3.2	1.75	3	3	0.125
FPO3-12	12'-0"	8.86	6.42	4.74	3.55	1.98	3	3	0.125
FPO4-15	15'-0"	11.89	8.46	6.11	4.42	2.23	4	4	0.125
DPO4-15	15'-0"	11.53	8.18	5.88	4.24	2.1	4	4	0.125
DPO/PLT-12	12'-0"	6.83	4.81	3.42	2.42	1.13	3	3	0.125
DPO/PLT-12/COV	12'-0"	6.83	4.81	3.42	2.42	1.13	3	3	0.125
FPO3/PLT-12	12'-0"	7.13	5.04	3.6	2.57	1.23	3	3	0.125
FPO3/PLT-12/COV	12'-0"	7.13	5.04	3.6	2.57	1.23	3	3	0.125
DPO4/PLT-08	8'-0"	21.03	15.74	12.11	9.52	6.15	4	4	0.125
DPO4/PLT-10	10'-0"	16.66	12.29	9.3	7.16	4.37	4	4	0.125
DPO4/PLT-12	12'-0"	13.45	9.73	7.18	5.36	2.98	4	4	0.125
DPO4/PLT-14	14'-0"	10.95	7.71	5.49	3.9	1.83	4	4	0.125
FPO4/PLT-08	8'-0"	22.21	16.65	12.83	10.1	6.55	4	4	0.125
FPO4/PLT-10	10'-0"	17.64	13.04	9.89	7.64	4.7	4	4	0.125
FPO4/PLT-12	12'-0"	14.29	10.37	7.69	5.77	3.26	4	4	0.125
FPO4/PLT-14	14'-0"	11.68	8.27	5.93	4.26	2.08	4	4	0.125
TPO43/PLT-08	8'-0"	21.33	16.04	12.42	9.83	6.45	4	3	0.125
TPO43/PLT-10	10'-0"	17.05	12.69	9.69	7.55	4.76	4	3	0.125
TPO43/PLT-12	12'-0"	13.93	10.21	7.66	5.84	3.46	4	3	0.125
TPO43/PLT-14	14'-0"	11.53	8.29	6.07	4.48	2.41	4	3	0.125
D1010-20	9'-3"	48.40	36.73	28.73	23.01	15.56	6 7/8	4 1/4	0.25
D1012-20	12'-3"	37.91	28.55	22.13	17.54	11.56	6 7/8	4 1/4	0.25
D1012-23	12'-4"	37.84	27.91	21.53	16.97	13.37	7 1/2	4 1/2	0.25
D1014-20	14'-0"	32.97	24.67	18.97	14.90	9.60	7 1/2	4 1/2	0.25
D1014-25	14'-0"	33.04	24.73	19.04	14.97	9.66	7 1/2	4 1/2	0.25
D1010S	10'-4"	33.39	26.07	19.64	15.64	10.43	6	4	0.25
1012S	12'-2"	42.76	32.23	25.01	19.85	13.12	7 1/4	4 1/2	0.25
1010-S14	9'-11"	34.33	25.94	20.19	16.08	10.72	6	4	0.25
1012-S14	11'-11"	28.60	21.46	16.56	13.06	8.49	6	4	0.25
D1310	10'-0"	34.36	25.97	20.22	16.11	10.75	6	4	0.25

Amerlux Exterior Pole EPA Table

Effective Projected Area In Sq. Ft. at:

Model Number	Pole Height	70 MPH	80 MPH	90 MPH	100 MPH	120 MPH	Diameter of Shaft at Base (Inches)	Diameter of Shaft Top (Inches)	Shaft Wall Thickness (Inches)
D1312	12'-0"	28.63	21.49	16.59	13.08	8.52	6	4	0.25
D1314	14'-0"	31.31	23.45	18.07	14.21	9.19	6 3/4	3 1/4	0.25
D2011	11'-3"	30.98	23.42	18.23	14.52	9.69	6	4	0.25
D2013	13'-4"	26.03	19.53	15.07	11.88	7.72	6	4	0.25
DSD17-10	10'-0"	34.51	26.13	20.38	16.26	10.90	6	4	0.25
DSD17-12	12'-0"	28.80	21.65	16.75	13.25	8.68	6	4	0.25
DSD20-11	11'-5"	30.36	22.94	17.85	14.21	9.47	6	4	0.25
DSD20-13	13'-6"	25.74	19.30	14.89	11.74	7.63	6	4	0.25
DSD20-13H	13'-5"	41.84	31.53	24.47	19.41	12.83	7 1/2	4 1/2	0.25
NOTE: THE ABOVE CALCULATIONS ARE BASED ON A LUMINAIRE WEIGHT OF 50 LBS OR LESS CENTERED ABOUT THE POLE									